

# Model F - Anchor Applicator

Rebuild Program



## Rebuild inclusions

The Model F - Anchor Applicator rebuild program includes the following:

- New, rebuilt, or re-qualified engine; Deutz engine standard, John Deere engine available
- New demountable-style axles
- New coast switch kit
- Upgraded boxing cylinder
- New or rebuilt pump
- New brake shoes, levers, and cylinders
- Rebuilt jaw and clamp arm assemblies
- Rebuilt chute assembly and cylinder
- New bushings
- New manifold and junction boxes
- Rebuilt and cleaned tanks
- Complete sandblast, repaint, and decal



Model F - Anchor Applicator

BEFORE



AFTER



Use your smartphone to scan this code for more information.

## Product Specifications

Category	Specification	Value
<b>General</b>	Weight	12,500 lbs (with boom only), 14,800 lbs (with boom, hydraulic dump bin, and canopy)
	Length	14' 4" (with bumpers), 13' 8" (without bumpers)
	Width	10' 5" (with sliding canopy extended), 8' 3" (with sliding canopy closed)
	Height	8' 10" (with boom only), 9' 5" (with boom and hydraulic dump bin)
	Wheel base	6' 4"
	Travel speed	25 mph (maximum)
<b>Capacities</b>	Fuel tank	39.7 gallons
	Hydraulic tank	100 gallons
<b>Engine</b>	Make/Model	Deutz BF4L1011, turbo-charged four-cylinder, four-stroke (standard), John Deere 4045D, 99 HP, four-cylinder, inline (optional)
<b>Hydraulic System</b>	Pumps	Vickers PVH Series
	Control valves	Vickers Manifolder
<b>Electrical System</b>	Battery	12 Vdc, 1150 cold-cranking amps
<b>Drive System</b>	Drive type	Two-wheel, one axle
<b>Wheels</b>	Wheel size and type	16-inch diameter, cast steel
<b>Brakes</b>	Type	Four-wheel shoe type, spring-actuated, hydraulic-release

[www.nordco.com](http://www.nordco.com)

245 W. Forest Hill Avenue  
 Oak Creek, WI 53154 USA  
 Phone: 414-766-2180  
 Fax: 414-766-2379

