



The Nordco Auto Lift automatically lifts one or both rails to a specific height, allowing positioning of the tie plates between the ties and rail. The self-propelled machine includes ergonomic controls and plate-pushing tools for increased productivity and operator comfort. The machine can insert plates under one or both rails. Plates are inserted from the field side.



www.nordco.com



STANDARD FEATURES

- 2 Integrated Plate Pusher Assemblies
- Simple Adjustments for Varying Rail Heights
- 12V Relay Logic Controlled Electrical System
- Microfast Cables with Limit Switches
- Parker Pump
- Hydraulic Oil Cooling System
- Easy to Access Steel Manifolds with Vickers Valves
- Dual Axle Chain Driven Propulsion System
- 4 Pin Clutch System
- Pressure and Suction Filtration
- Strobe, Travel and Work Lights
- Roller Clamps Used for Lifting Rail
- Heavy Duty Cylinders for Lifting Machine
- Storage Area for Additional Plates



OPTIONAL EQUIPMENT

- Jack Stands
- Night Lighting Package
- Tow Bar
- 18 Gallon Fuel Tank
- Parking Brake
- Cold Weather Hydraulic Warm Up

This is a list of frequently ordered options. Additional options are available. Contact Nordco Sales for more information.

This document is for general reference purposes only. Specifications are subject to change and may vary by machine.

SPECIFICATIONS:

General

Weight4,500 lbs
Length7' 10"
Width6' 8"
Height9' 0"
Wheels14" Cast Steel

Capacities

Fuel Tank10 Gallons
Hydraulic Tank30 Gallons

Engine

23 HP 2 Cylinder Diesel Fired Engine

Hydraulic System

PumpParker PAVC 65
Control ValvesVickers
Oil CoolerElectric Fan

Electrical System

12 VDC