



The Nordco Anchor Applicator Model F simultaneously applies two anchors while boxing ties. The large anchor storage bin is sufficient for a single string of rail. Anchors are positioned in front of the operator for maximum productivity. Its chute design keeps the operator's hands away from the anchor-applying tool. Anchors are held by the clamping assembly which swings down under the rail, boxes the ties, and snaps the anchor in place in a single, smooth operation. Controls are conveniently placed and adjustments for varying rail heights are easy to make. Operator visibility is excellent for both work and travel.

www.nordco.com



STANDARD FEATURES

- Seating for 1 Operator
- Windshield and Wipers at Operators Station
- Sliding Canopy Over Work Station
- Tilttable Storage Bin for Anchor Storage
- Boom and Winch Assembly for Loading Anchors in Bin
- Hydraulic Powered Guide Roller Assemblies
- Easy to Access Steel Manifolds with Vickers Valves
- Demountable Style Axle Assemblies with Cobra Brake Shoes
- Spring-Applied, Hydraulic Release Braking System
- Dual-Axle, Chain-Driven Propulsion System
- Simplified Feed System – Easily Adapted to Other Fasteners



OPTIONAL EQUIPMENT

- Jack Stands
- Night Lighting Package
- Tow Bar
- Curtains to Protect Operators from Harsh Elements
- Electric Top Off – Hydraulic System
- Electric Emergency Pump
- Increased Capacity Storage Bin with Funnel for Bulk Loading

This is a list of frequently ordered options. Additional options are available. Contact Nordco Sales for more information.

This document is for general reference purposes only. Specifications are subject to change and may vary by machine.

SPECIFICATIONS:

General

Weight17,750 lbs
 Length15'
 Width8' 4"
 Height9' 2"
 Wheels16" Cast Steel

Capacities

Fuel Tank40 Gallons
 Hydraulic Tank98 Gallons

Engine

99 HP 4 Cylinder Diesel Fired Engine

Hydraulic System

PumpVickers PVM 57
 Control ValvesVickers Manifoldd
 Oil CoolerElectric Fan, 80 GPM

Electrical System

12 VDC

www.nordco.com

