

# Regulators

Models KL, M, G2 and Groundhog  
Rebuild Program



## Rebuild inclusions

Regulators can be rebuilt with either ballast or snowplowing equipment. The Regulator rebuild program includes the following:

- New Tier III engine
- Rebuilt axles
- New or rebuilt pump
- New brake shoes, levers, and cylinders
- Rebuilt cab assembly
- Rebuilt brooms, wings and plow
- Cleaned and rebuilt tanks
- Reinforced frame
- Option to upgrade to variable-volume, hydraulic-release brake system
- Complete sandblast, repaint, and decal
- New machine warranty



Front View, Rebuilt Ballast Regulator

BEFORE



AFTER



Use your smartphone to scan  
this code for more information.

## Optional Equipment

Category	Option Type	Description
<b>Ballast</b>	Wings	Rotational ballast wings
<b>Snow/Winter</b>	Snow/Winter-related accessories	Stairs on broom shroud, snow wings, and snow auger, 110V hydraulic tank heater, 16 ft-reach snow wings, additional lower snow curls, brake de-icing feature, cab-controlled power lockups for snow wings, center flanging plate, Espar airtronic 4 diesel-fired cab heater, Espar diesel-fired engine heater, high-speed V-plow, second operator's suspension seat, snow screw and blower, upper snow curls for front plow
<b>Repair &amp; Maintenance</b>	Lubrication System	Electric top-off pump
	Schroeder test mates	Filters oil to remove engine wear-related metal filings
<b>Other Accessories</b>	Gauges and alarms	Fuel level site gauge, hydraulic reservoir temperature gauge, low hydraulic oil level/high hydraulic oil temperature alarm, hydraulic tank fluid level gauge, hydraulic system pressure gauges
	Lighting and Mirrors	Dome light in engine compartment, electrical cabinet light, locomotive headlights, perimeter lighting package, additional rear view mirror
	Storage	Storage box, additional book storage box
	Miscellaneous	"Danger Live Track" chain-mounted signs, DOT reflective tape, extra parts/operations/maintenance manuals, tow bar with D-handle hitch pins, side window wipers, auxiliary air compressor, 4" vise welded to machine, wheel fenders
	Turntable	Safety interlock and low turntable warning, spring-loaded lock on turntable

## Product Specifications

Category	Specification	Value
<b>General</b>	Weight	43,000 lbs
	Length	31'
	Width	10' 2" (with wings in up and locked position)
	Working Clearance	14' 1" (from center of track with one fixed wing extended)
	Height	11' 9"
	Wheel Base	13' 5"
	Travel Speed	40 mph (maximum)
<b>Capacities</b>	Fuel Tank	90 gallons
	Hydraulic Tank	114 gallons
<b>Engine</b>	Make/Model	John Deere 6068THF485, Tier III, turbo-charged, six-cylinder
<b>Hydraulic System</b>	Track Drive Pumps	Sauer Danfoss 90 Series
	Implement and Blower Pumps	Sauer Danfoss 45 Series
<b>Electrical System</b>	Battery	24 Vdc (dual 12V DC batteries), 1150 cold-cranking amps
<b>Axle Drive System</b>	Drive Type	Dual-axle, chain-drive, hydraulic motor driven
<b>Brakes</b>	Type/Style	Cobra-style

[www.nordco.com](http://www.nordco.com)

245 W. Forest Hill Avenue  
 Oak Creek, WI 53154 USA  
 Phone: 414-766-2180  
 Fax: 414-766-2379

