CGS - Curve Gang Spiker







Key Features

The CGS - Curve Gang Spiker includes the following key features:

- Semi-enclosed cab, with seating for one spiker operator and one feed-tray operator
- Reciprocating hammer spike drivers; Lewis bolt workheads available
- Remote, electric spike-pattern adjustments
- Digital, variable roller gager
- · Tie nipper
- Boom and winch for loading spike kegs; optional bulk loader/Cluster Buster option available
- Positive locking turntable with steel base
- · John Deere Tier IV diesel engine
- 24 VDC, circuit breaker-protected, electrical system
- · Cobra brake shoes
- Four-wheel, dual-axle, chain and sprocket propulsion system
- Single, pressure-compensated, hydraulic pump
- · Joystick controls

Digital roller gager allows gauging and spiking with one machine.

Ideal for rail changing operations

The digital, variable roller gager allows the CGS - Curve Gang Spiker to set rail gauge distances as well as perform spiking operations. The guide wheels stabilize the rail during gauging and spiking activities. The easy-to-operate, single-sided CGS features fast and powerful spike driving action using a CX Hammer-type workhead.

Compact and lightweight

The CGS is compact and lightweight, making it simple to load and unload. In addition, the machine's open, modular design makes it easy to maintain.

Quickly adjust to different working conditions

Make simple adjustments - from inside the cab - to adapt the gun spacing for different hole patterns. Or quickly set the proximity switches to adjust the workhead to handle different rail heights. In addition, easily switch between settings for welded or jointed rail.

Bridges? No problem.

The optional bridge rail roller assembly allows the CGS - Curve Gang Spiker to spike tie plates on bridge rails.

Quickly load spikes

Use the attached boom and winch to quickly load spike kegs onto the rear storage rack; the winch handles loads up to 300 lbs. Or, include the optional bulk loader to use bulk spikes.

Intuitive joystick controls and excellent operator visibility allow increased precison during spike driving.





The included digital roller gauger allows gauging and spiking with one machine.



Ask us about...

Rebuild Programs

Are your maintenance-of-way machines getting older and less reliable? Nordco can rebuild virtually all maintenance-of-way equipment, regardless of original manufacturer, restoring your machines to like-new status.

Component Exchange Programs

Do you only need a replacement component, such as a workhead or axle, for your maintenance-of-way machine? You can order new or rebuilt components to be delivered directly to your shop or field operations.

Trade-In Programs

Interested in purchasing a new maintenance-of-way machine, but wondering what to do with your existing equipment? In many cases, you can trade in your current equipment for credit towards a new machine.

Rental Programs

Have a short-term need for a particular maintenance-of-way machine? Check our website for a current list of available rental equipment.

Parts Availability

Need parts for your maintenance-of-way machine? Contact our part experts at 1-800-647-1724, Monday through Friday, 7:30 a.m. to 5:00 p.m. US Central Time.

Want to ensure that you order the most essential parts to keep your maintenance-of-way machine operational? Check our website or ask your parts sales representative about the available critical component kits and basic spare part kits for your machine.

Not sure what parts to order for preventive maintenance or winterization? You'll find a large range of kits available - check our website or ask your parts sales representative.

Optional Equipment

Category	Option Type	Description
Cab	Cab accessories	Cab-controlled power locks (workheads, nipper and gager), cab pressurizer, cab window shades, engine-driven air conditioner, spike feeder swivel seat pedestal, engine-driven air conditioner (red dot)
Spike Control	Spike accessories	Push-style bulk loader, Cluster-Buster/spring-mount option for bulk loader, dust collection system for bulk spike loader, ladder and walkway for bulk loader, steps and grab irons for bulk loader maintenance access, Lewis bolt/Evergrip driving heads (one side)
Repair & Maintenance	Corner-mounted jackstands	Holds the unit above the track to allow under-machine repairs
	Electric hydraulic tank fill system	Allows quick filling of hydraulic tank
	Spare hose tree	Stores extra hoses on the machine
	Remote coolant filter loops / Remote fluid drains	Allows quick filter/fluid maintenance
	Schroeder KF 30 case drain return filtration	Filters oil to remove engine wear-related metal filings
	Electric emergency pump	Allows workhead to be moved if engine fails
Other Accessories	Gauges and alarms	Fuel level site gauge, speedometer, hydraulic reservoir temperature gauge, low hydraulic oil/high hydraulic oil temperature alarm
	Lighting and mirrors	Heated outside mirrors, perimeter lighting package
	Storage	Additional book storage box, track tool box
	Miscellaneous	"Danger Live Track" retractable belt, DOT reflective tape, extra parts/operations/maintenance manuals, rail sweeps, tow bar with D-handle hitch pins, windshield washer fluid tankand nozzles
	Turntable	Aluminum replacement for standard steel turntable, turntable warning light and buzzer

Product Specifications

Category	Specification	Value
General	Weight	11,500 lbs (empty spike bin); 12,300 lbs. (full spike bin)
	Length	16′ 2″
	Width	8′ 4″
	Height	8′ 6″
	Wheel base	10′ 4.75″
	Travel speed	25 mph (maximum)
Capacities	Fuel tank	35 gallons
	Hydraulic tank	40 gallons
Engine	Make/Model	John Deere 4024T, Tier IV
	Туре	Turbocharged, inline four-cylinder
Hydraulic System	Make/Model	Vickers PVM057 (24 volt)
	Туре	Pressure-compensated, variable displacement piston pump
Electrical System	Battery	24 Vdc (dual 12V DC batteries), 1150 cold-cranking amps
Axle Drive System	Drive type	Dual-axle chain drive
	Propulsion motor type	Hydraulic
Brakes	Туре	Four-wheel Cobra-style, spring-actuated, hydraulic release

www.nordco.com

245 W. Forest Hill Avenue Oak Creek, WI 53154 USA Phone: 414-766-2180 Fax: 414-766-2379

