

Super Claws - Single-Sided Spike Puller

Rebuild Program



Rebuild inclusions

The Super Claws - Single-Sided Spike Puller rebuild program includes the following:

- New engine
- New battery
- New Model C-style controllers
- New roller frame and toggle slide plates
- New claw levers and claws
- New ductile manifold assemblies and valves
- New junction boxes and cabling
- New 24V logic box assembly
- New or rebuilt axle assemblies
- New or rebuilt cylinders
- New wiring and hosing
- Cleaned and tested tanks
- Added strobe lights and work lights
- Complete sandblast, repaint, and decal



Super Claws - Single-Sided Spike Puller - Post-Conversion



BEFORE



AFTER



Use your smartphone to scan this code for more information.

Product Specifications

Category	Specification	Value
General	Weight	7,250 lbs
	Length	14'
	Width	7' 6"
	Height	8' 6"
	Wheel base	84"
	Travel speed	25 mph (maximum)
Capacities	Fuel tank	12.8 gallons
	Hydraulic tank	32.5 gallons
Engine	Make/Model	John Deere 4024D, Tier III, four-cylinder
Hydraulic System	Pumps	Sauer Danfoss Series 45, J-frame, open-circuit axial piston pump
	Control valves	Vickers Manifolded
Electrical System	Battery	24 Vdc, 1150 cold-cranking amps
Axle System	Drive type	Hydraulic, dual-axle chain drive
Wheels	Wheel size and type	6-inch diameter, cast steel
Brakes	Type	Four-wheel shoe type, spring-actuated, hydraulic-release, deadman

www.nordco.com

245 W. Forest Hill Avenue
 Oak Creek, WI 53154 USA
 Phone: 414-766-2180
 Fax: 414-766-2379

