TRIPP - Tie Exchanger

Rebuild Program



Rebuild inclusions

The TRIPP - Tie Exchanger rebuild program includes the following:

- New Tier III engine; Tier IV upgrade available
- Rebuilt and upgraded rail lift workhead
- Rebuilt cab assembly
- Rebuilt and upgraded tie exchanger workhead
- Rebuilt ductile manifold assemblies
- New Micro-fast cabling
- · New or rebuilt cylinders
- New wiring and hosing
- Complete sandblast, repaint, and decal
- New machine warranty



TRIPP - Tie Exchanger











Optional Equipment

Category	Option Type	Description
Cabin	Cabin accessories	Cab window shades, vandal guards (protective screens over cab windows)
Tie Control	Tie-related accessories	Concrete tie grippers (1 pair), rail lift spotting feature, tie insertion stop device, upgrades to make machine suitable for work in third-rail territory
Engine	Engine upgrade	John Deere Tier IV diesel engine
Repair & Maintenance	Lubrication system	Air-powered grease lubrication system (35# pail & 32' hose)
	Electric hydraulic tank fill system	Allows quick filling of hydraulic tank
	Spare hose tree	Stores extra hoses on the machine
	Remote coolant filter loops	Allows quick filter maintenance
	Schroeder KF 30 case drain return filtration	Filters oil to remove engine wear-related metal filings
	Drive axles	Cab-selectable insulation by-pass for drive axles
Other Accessories	Gauges and alarms	Fuel level site gauge, speedometer, hydraulic reservoir temperature gauge, low hydraulic oil level/high hydraulic oil temperature alarm
	Lighting and mirrors	Heated outside mirrors, perimeter lighting package
	Storage	Additional book storage box, track tool box
	Miscellaneous	"Danger Live Track" retractable belt, DOT reflective tape, extra parts/operations/maintenance manuals, rail sweeps, tow bar with D-handle hitch pins, windshield washer fluid tankand nozzles
	Turntable	Aluminum replacement for standard steel turntable, turntable warning light and buzzer

Product Specifications

Category	Specification	Value
General	Weight	36,000 lbs
	Length	36'
	Width	11'
	Working clearance	12' 1" (from center of track with one tie exchanger extended)
	Height	11′ 6″
	Wheel base	25'
	Travel speed	23 mph (maximum)
Capacities	Fuel tank	120 gallons
	Hydraulic tank	2 @85 gallons
Engine	Make/Model	John Deere 6068T, Tier IV, turbo-charged, six-cylinder
Hydraulic System	Pumps	Oil Gear PVG
	Control valves	Piston pump
Electrical System	Battery	24 Vdc (dual 12V DC batteries), 1150 cold-cranking amps
Axle Drive System	Drive type	Dual-axle, chain-drive, hydraulic
Brakes	Type/Style	Pneumatically-applied (air), four-wheel, Cobra-style

www.nordco.com

245 W. Forest Hill Avenue Oak Creek, WI 53154 USA Phone: 414-766-2180 Fax: 414-766-2379

